

Paper 36: FRICTION-BASED FORCE-LIMITING CONNECTIONS FOR EARTHQUAKE-RESISTANT BUILDINGS

Georgios Tsampras 1, Kaixin Chen 2, Kyoungyeon Lee 3

1 Department of Structural Engineering, University of California San Diego, La Jolla, San Diego, CA 92093, USA, gtsampras@ucsd.edu .

2 Department of Structural Engineering, University of California San Diego, La Jolla, San Diego, CA 92093, USA, kac011@ucsd.edu .

3 Department of Structural Engineering, University of California San Diego, La Jolla, San Diego, CA 92093, USA, kyl008@ucsd.edu .

Practical force-limiting connections between the floor-diaphragms and the vertical elements of the seismic force resisting systems in buildings have been developed [1]–[7]. The use of force-limiting connections (1) limits the force and acceleration responses of buildings (2) reduces the variability in the force and acceleration responses due to the ground motion variability, and (3) mitigates the effects of higher mode responses on the dynamic responses of buildings. Friction-based force-limiting connections can be designed to remain undamaged during earthquakes, and they can be reused after earthquakes. They are axially stiff, compact, easy-to-assemble, and can accommodate the seismic-induced three-dimensional kinematic requirements. The force-displacement response of friction-based force-limiting connections depends on the effect of machining tolerances, the materials used in the frictional interface (i.e., metallic and non-metallic materials), and the characteristics and the sequence of the loading displacement history (i.e., dwell-time, sliding velocity, cumulative sliding, and breakin effect). This presentation focuses on results from large scale tests of friction-based forcelimiting connections. It highlights the limitations and needs for future research related to the use of practical friction-based force-limiting connections in earthquake resistant buildings.

References:

[1] S. T. Crane, “Influence of energy dissipation connections between floors and the lateral force resisting system,” UC San Diego, USA, 2004.

[2] D. Zhang et al., "Development of a Floor Inertial Force Limiting Anchorage System Building Seismic Response," in 10th U.S. National Conference on Earthquake Engineering, 2014, p. 11.

[3] G. Tsampras et al., "Development of deformable connection for earthquake-resistant buildings to reduce floor accelerations and force responses," Earthquake Engineering & Structural Dynamics, vol. 45, no. 9, pp. 1473–1494, Jul. 2016, doi: 10.1002/eqe.2718.

[4] G. Tsampras, R. Sause, R. B. Fleischman, and J. I. Restrepo, "Experimental study of deformable connection consisting of buckling-restrained brace and rubber bearings to connect floor system to lateral force resisting system," Earthquake Engineering & Structural Dynamics, vol. 46, no. 8, pp. 1287–1305, Jul. 2017, doi: 10.1002/eqe.2856.

[5] G. Tsampras, R. Sause, R. B. Fleischman, and J. I. Restrepo, "Experimental study of deformable connection consisting of friction device and rubber bearings to connect floor system to lateral force resisting system," Earthquake Engineering & Structural Dynamics, vol. 47, no. 4, pp. 1032–1053, 2018, doi: 10.1002/eqe.3004.

[6] Z. Zhang et al., "Shake-table test performance of an inertial force-limiting floor anchorage system," Earthquake Engineering & Structural Dynamics, vol. 47, no. 10, pp. 1987–2011, 2018, doi: https://doi.org/10.1002/eqe.3047.

[7] G. Tsampras and R. Sause, "Force-based design method for force-limiting deformable connections in earthquake-resistant buildings," Journal of Structural Engineering, Under Review, 2022.